

L4 ANSWER 10 OF 561 CA COPYRIGHT 2004 ACS on STN  
 AN 140:6222 CA  
 ED Entered STN: 25 Dec 2003  
 TI Water-soluble fireproofing composition with good elasticity and  
 adhesion to substrates  
 IN Masini, Giovanni  
 PA Italy  
 SO Ital., 10 pp.  
 CODEN: ITXXBY  
 DT Patent  
 LA Italian  
 IC ICM C09D  
 CC 42-7 (Coatings, Inks, and Related Products)  
 Section cross-reference(s): 55

FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	IT 1311962	B1	20020320	IT 1999-GE130	19991104
PRAI	IT 1999-GE130		19991104		
AB	The coating compn. with high adhesion to ferrous materials comprises 35-45 parts inorg. inert compd., 25-35 parts pozzolan cement, 18-20 parts hydrated alumina, 0 - 5 parts titania, 02 parts Al silicate, 3-3.5 parts film forming agent, 0.03-0.08 parts fluidizing agent, 0.10-0.20 rosin soap, 0.05 - 0.15 parts stabilizer, and at least 30% water. The inorg. inert compd. is selected from CaCO <sub>3</sub> , quartz flour, or powd. minerals, the film forming agent is selected from styrene-acrylic resins and ethylene-vinyl acetate copolymer, and the stabilizer is selected from starch and carboxymethylated starch.				
ST	fireproofing coating high solids calcium carbonate acrylic binder; pozzolan cement alumina silicate EVA binder fireproofing coating; metal fireproofing waterborne coating adhesion elasticity				
IT	Coating materials (fire-resistant; high-inorg. solids water-sol. fire-resistan				